

VZCA2.E527857 - Surge-protective Devices - Component

Surge-protective Devices - Component

Flow Semiconductor Co., Ltd

E527857

Room 501, Building 6, Kodatsu Manufacturing, 310 Pine Road, Liaobu, Dongguan, Guangdong, China
 Dongguan, GUANGDONG 523406 China

Cat. No.	SPD Type	Volts (V)	AC/DC/ DC PV	PH	AMPS		MODE	VPR (Vpk)	MLV (Vpk)	MCOV (V)	Vn (Vdc)	in (kA)	SCCR (kA)	Notes	
					(A)	(°C)									Min (°C)
2R075@L-&X	5	24	AC	1	N/A	-40	105	Ld-Ld	-	1290	24	N/A	10	N/A	1, 3
2R075@M-&X	5	24	AC	1	N/A	-40	105	Ld-Ld	-	1290	24	N/A	10	N/A	1, 3
2R090@L-&X	5	24	AC	1	N/A	-40	105	Ld-Ld	-	1290	24	N/A	10	N/A	1, 3
2R090@M-&X	5	24	AC	1	N/A	-40	105	Ld-Ld	-	1290	24	N/A	10	N/A	1, 3
2R1000@L-&X	5	275	AC	1	N/A	-40	105	Ld-Ld	-	1960	275	N/A	10	N/A	1, 3
2R1000@M-&X	5	275	AC	1	N/A	-40	105	Ld-Ld	-	1960	275	N/A	10	N/A	1, 3
2R1200@L-&X	5	275	AC	1	N/A	-40	105	Ld-Ld	-	2190	275	N/A	10	N/A	1, 3
2R1200@M-&X	5	275	AC	1	N/A	-40	105	Ld-Ld	-	2190	275	N/A	10	N/A	1, 3
2R1400@L-&X	5	500	AC	1	N/A	-40	105	Ld-Ld	-	2920	500	N/A	10	N/A	1,3
2R1400@M-&X	5	500	AC	1	N/A	-40	105	Ld-Ld	-	2920	500	N/A	10	N/A	1,3
2R1500@L-&X	5	500	AC	1	N/A	-40	105	Ld-Ld	-	3080	500	N/A	10	N/A	1, 3
2R1500@M-&X	5	500	AC	1	N/A	-40	105	Ld-Ld	-	3080	500	N/A	10	N/A	1, 3
2R150@L-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1580	220	N/A	10	N/A	1, 3
2R150@M-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1580	220	N/A	10	N/A	1, 3

2R1600@L-&X	5	500	AC	1	N/A	-40	105	Ld-Ld	-	3100	500	N/A	10	N/A	1, 3
2R1600@M-&X	5	500	AC	1	N/A	-40	105	Ld-Ld	-	3100	500	N/A	10	N/A	1, 3
2R2000@L-&X	5	500	AC	1	N/A	-40	105	Ld-Ld	-	2950	500	N/A	5	N/A	1, 3
2R2000@M-&X	5	500	AC	1	N/A	-40	105	Ld-Ld	-	2950	500	N/A	5	N/A	1, 3
2R200@L-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1610	220	N/A	10	N/A	1, 3
2R200@M-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1610	220	N/A	10	N/A	1, 3
2R230@L-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1610	220	N/A	10	N/A	1, 3
2R230@M-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1610	220	N/A	10	N/A	1, 3
2R2500@L-&X	5	500	AC	1	N/A	-40	105	Ld-Ld	-	3260	500	N/A	5	N/A	1, 3
2R2500@M-&X	5	500	AC	1	N/A	-40	105	Ld-Ld	-	3260	500	N/A	5	N/A	1, 3
2R250@L-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1610	220	N/A	10	N/A	1, 3
2R250@M-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1610	220	N/A	10	N/A	1, 3
2R2700@L-&X	5	500	AC	1	N/A	-40	105	Ld-Ld	-	3690	500	N/A	5	N/A	1, 3
2R2700@M-&X	5	500	AC	1	N/A	-40	105	Ld-Ld	-	3690	500	N/A	5	N/A	1, 3
2R3000@L-&X	5	500	AC	1	N/A	-40	105	Ld-Ld	-	3950	500	N/A	5	N/A	1, 3
2R3000@M-&X	5	500	AC	1	N/A	-40	105	Ld-Ld	-	3950	500	N/A	5	N/A	1, 3
2R300@L-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1620	220	N/A	10	N/A	1, 3
2R300@M-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1620	220	N/A	10	N/A	1, 3
2R350@L-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1650	220	N/A	10	N/A	1, 3
2R350@M-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1650	220	N/A	10	N/A	1, 3
2R3600@L-&X	5	500	AC	1	N/A	-40	105	Ld-Ld	-	5050	500	N/A	3	N/A	1, 3

2R3600@M-&X	5	500	AC	1	N/A	-40	105	Ld-Ld	-	5050	500	N/A	3	N/A	1, 3
2R400@L-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1620	220	N/A	10	N/A	1, 3
2R400@M-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1620	220	N/A	10	N/A	1, 3
2R470@L-&X	5	230	AC	1	N/A	-40	105	Ld-Ld	-	1610	230	N/A	10	N/A	1, 3
2R470@M-&X	5	230	AC	1	N/A	-40	105	Ld-Ld	-	1610	230	N/A	10	N/A	1, 3
2R600@L-&X	5	275	AC	1	N/A	-40	105	Ld-Ld	-	1790	275	N/A	10	N/A	1, 3
2R600@M-&X	5	275	AC	1	N/A	-40	105	Ld-Ld	-	1790	275	N/A	10	N/A	1, 3
2R800@L-&X	5	275	AC	1	N/A	-40	105	Ld-Ld	-	2240	275	N/A	10	N/A	1, 3
2R800@M-&X	5	275	AC	1	N/A	-40	105	Ld-Ld	-	2240	275	N/A	10	N/A	1, 3
3R075@L-&X	5	24	AC	1	N/A	-40	105	Ld-Ld	-	1230	24	N/A	10	N/A	1, 3
3R075@M-&X	5	24	AC	1	N/A	-40	105	Ld-Ld	-	1230	24	N/A	10	N/A	1, 3
3R090@L-&X	5	24	AC	1	N/A	-40	105	Ld-Ld	-	1230	24	N/A	10	N/A	1, 3
3R090@M-&X	5	24	AC	1	N/A	-40	105	Ld-Ld	-	1230	24	N/A	10	N/A	1, 3
3R150@L-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1550	220	N/A	10	N/A	1, 3
3R150@M-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1550	220	N/A	10	N/A	1, 3
3R230@L-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1550	220	N/A	10	N/A	1, 3
3R230@M-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1550	220	N/A	10	N/A	1, 3
3R250@L-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1550	220	N/A	10	N/A	1, 3
3R250@M-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1550	220	N/A	10	N/A	1, 3
3R350@L-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1550	220	N/A	10	N/A	1, 3
3R350@M-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1550	220	N/A	10	N/A	1, 3

3R400@L-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1530	220	N/A	10	N/A	1, 3
3R400@M-&X	5	220	AC	1	N/A	-40	105	Ld-Ld	-	1530	220	N/A	10	N/A	1, 3
3R470@L-&X	5	230	AC	1	N/A	-40	105	Ld-Ld	-	1560	230	N/A	10	N/A	1, 3
3R470@M-&X	5	230	AC	1	N/A	-40	105	Ld-Ld	-	1560	230	N/A	10	N/A	1, 3
3R600@L-&X	5	275	AC	1	N/A	-40	105	Ld-Ld	-	1720	275	N/A	10	N/A	1, 3
3R600@M-&X	5	275	AC	1	N/A	-40	105	Ld-Ld	-	1720	275	N/A	10	N/A	1, 3

Notes:

1. Suitable for Factory wiring only.
 2. Suitable for Field and Factory wiring.
 3. Series External Impedance required, see Electrical Ratings in the Recognition report.
 4. Series External Overcurrent Protection required, see Electrical Ratings in the Recognition report.
 5. Body of discrete component metal-oxide varistors (MOVs) flammability:
 - a) Min. V-0 or VTM-0.
 - b) Min. V-1 or VTM-1.
 - c) Complies with IEC 60950-1, Edition 2.2, Annex Q/IEC62368-1 Annex G.8.2 needle flame testing requirements.
 - d) Complies with IEC 60065, Edition 7.2, Annex G.1.1 needle flame testing requirements.
 6. Complies with Stress Test Qualification per AEC-Q200 Rev D.
 7. Suitable for Damp Location use:
 - a) 85C/85% relative humidity
 - b) 40C/93% relative humidity
- & - 1 digit with any number or letters 0~9, A~Z.
- @ - 1 digit with any number or letters 0~9, A~Z, or blank.
- X - 1 digit with any number or letters 0~9, A~Z, or blank.

Marking: Company name or trademark  ,  ,  ,  ,  and model designation and the Recognized Component Mark, .



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with

permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."